

# ELSTER KENT V100T PSM Volumetric Water Meter Range

Tested, Tried and Trusted





**The V100T PSM Elster Kent Volumetric Water Meter is the world's favourite domestic water meter with over 50 million already in service in over 100 countries and offer accuracy, long life, low maintenance and tamperproof operation.**

Available in sizes from 15mm to 25mm, with flow rates of between 5.7 l/h to 7 m<sup>3</sup>/h, V100T PSM meters offer unrivalled performance to SABS 1529-1 Class C (for 15mm to 25mm only). In addition, models can provide valuable management information via a probe pulse unit upgrade.

- The world's biggest-selling domestic water meter
- Optimum accuracy and performance at all times, in any position
- Revolutionary grooved piston for improved durability and performance
- Durable tamperproof construction
- Full range of sizes from 15mm to 25mm
- Water temperatures up to 50°C
- Maximum working pressure of 16 bar
- Standard pulse output providing access to management information (reed switch optional extra)

#### The V100T PSM Elster Kent Volumetric Water Meter





### **Revolutionary grooved piston**

Meter stoppages are substantially reduced, durability enhanced and performance improved as a result of a uniquely-designed grooved piston within the meter measuring chamber, increasing applications flexibility. (available in 15mm and 20mm sizes)

### **Relative motion of the grooved piston**

Its action, with the stationary chamber wall, creates small flow eddies which hold solids in suspension until flushed out, reducing meter stoppages

---

### **Unrivalled accuracy in any position, for any flow**

Due to the volumetric rotary piston measurement principle, the V100T PSM range can achieve the highest levels of reading accuracy even at the lowest flow rate. The meter can be installed in any position ie: horizontally, vertically or inclined pipelines, maintaining optimum performance with no loss of accuracy.

### **Robust, leak-proof construction**

The use of advanced engineering plastics for the meter's measuring chamber significantly reduces wear and helps maintain reliable, accurate measurement over all operating conditions. Solid particles are gathered by a large surface area strainer, further preventing damage; and its advanced design ensures that partial obstruction of the strainer will have no ill effect on the accuracy of the meter's registration. A body 'O' ring seal between the measuring chamber and meter body ensures that internal leaks which could by-pass the measuring chamber are eliminated.

### **Easy to read**

The all-in-one counter and gear unit is fully sealed, liquid filled using a vacuum and offers simple, straight-reading presentation.

The number rollers are completely immersed in a lubricating non-toxic liquid, and a sac attached to the counter casing acts as a balancing membrane, ensuring the pressure of the liquid in the counter equals that of the external water. The counter window is inside the meter body in the direction of flow for simplified reading.

### **Tamperproof operation**

The V100T PSM offers unrivalled resistance to illegal tampering: its unique conical body-half design eliminates the risk of disassembly whilst in service and the mechanically driven cyclometer-type counter is resistant to magnetic interference. Non-return valve provides further protection against outside interference, preventing the meter being operated in the reverse direction to reduce the reading. This restrictor cannot be removed without opening the meter and destroying the seal.

### **Reliability guaranteed**

Every V100T PSM meter is individually tested over its flow range before despatch, and is manufactured from the highest quality materials ensuring maximum resistance to wear and corrosion. All Elster Kent meters are UK WRc approved to prevent health risk.


# V100T PSM

## Specifications Class C to SABS 1529-1

Meter size (mm)			15	20	25
Overload flow rate	$q_s \pm 2\%$	$m^3/h$	3	5	7
Permanent flow rate	$q_p \pm 2\%$	$m^3/h$	1.5	2.5	3.5
Transitional flow rate	$q_t \pm 2\%$	$l/h$	22.5	37.5	52.5
Minimum flow rate	$q_{min} \pm 5\%$	$l/h$	15	25	35
Starting flow (approximate)		$l/h$	5.7	9.5	13.2
Output pulse		litre/pulse	0.5	0.5	5
Meter diameter		mm	86	86	104
Meter length preferred		mm	165	190	198
Meter length alternative		mm	114	165	
Length over connectors		mm		267	311
Weight - Meter only (approximate)		kg	0.80	1.30	1.30

## Pressure Drop Graph


Pressure Drop Graphs  
(Typical) 15, 20 & 25mm  
PSM water meters



## Typical Flow Graph

### Warranty

All goods are tested and inspected prior to despatch. In the event of defects resulting from faulty workmanship or materials, such goods will be replaced/repared at our discretion, free of charge at the factory, but no responsibility will be accepted for any direct or consequential damage. This warranty covers the malfunction of a correctly installed item due to a manufacturing fault, but does not cover wear and tear considered normal at the locality of installation. Meter warranty 5 years from date of manufacture.



### Typical Specification:

15mm V100T PSM DZR brass bodied water meter of the semi-positive rotary piston type, 114mm long with non-return valve, fitted with a straight-reading counter and fixed one pulse per 1/2 litre output facility registering in  $m^3$  and approved under the Trade Metrology Act and Regulations and to SABS 1529-1: 1994 Class C Specifications.



**elster**  
Kent Metering (Pty) Ltd  
PO Box 201 Auckland Park 2006  
www.elsterkent.co.za

**JOHANNESBURG**  
Tel: (011) 470-4900  
Fax: (011) 474-0175

**DURBAN**  
Tel: (031) 266-4915  
Fax: (031) 266-9521

**CAPE TOWN**  
Tel: (021) 511-8465/6  
Fax: (021) 511-8446

**BLOEMFONTEIN**  
Tel: (051) 430-2603  
Fax: (051) 435-1455

**PORT ELIZABETH**  
Tel: (041) 363-1943/2026  
Fax: (041) 363-2127

The company's policy is one of continuous improvement and the right is reserved to modify the specifications without notice

40005/8/2008